

E700, 700 GD Pizza/Pastry Ovens



Model E700 GD Shown

E700 PIZZA/PASTRY OVEN

Designed for pizza or pastry baking.

E700 GD PIZZA OVEN

Ideal for pizza cooking. Has triple glazed door

FEATURES:

- Built in file hearth giving excellent heat retention and more even temperature,
- Can cook directly on to the filed hearth.
- Adjustable ventilating system on each oven,
- One hour minute timer.
- Stainless steel shelf between the legs of one and two deck units.
- Wire oven rack.
- Units can be supplied in single, double, or triple decks to either pastry or pizze ovens, or a combination of both.
- Further ovens may be added at a later date to form up to a litree deck unit.

PERFORMANCE:

Approximately 45 minutes required to raise the oven temperature from ambient to 250°C.

CONTROLS

MODELS 700 AND 700 GD: Thermostatically controlled oven temperature with separate regulators for top inner and outer elements. Single 3 heat switch controls both bottom elements.

Oven thermostal graduated from 120°C to 355°C.


Pilot light to indicate that over is at "set temperature" on both models.


FINISH:


External panels grey hammerlux enamel. Legs grey hammerlux enamel. Frontage and door stainless steel.



≠ E700, 700 GD Pizza/Pastry Ovens











ISO 9001

All Blue Seel products are designed and manufactured by Mattal using the internationally recognised ISO 9001 quality management system, cavaring design, manufacture and final inspection, ensuring consistent high quality at all times.

MODEL	NUMBER OF DECKS	DIMENSIONS		
		'A"	'B'	'C'
700 Pastry Oven (plain door) 700 GD Pizza Oven (glass	Single E700	1300mm (51")	775mm (30%")	255mm (10")
door)	Double £700/2 Triple £700/3	1655mm (65%") 1655mm (65%")		255mm (10") 255mm (10")

OVEN CAPACITY:

700 PASTRY & 700 GD PIZZA OVEN:

915mm wide \times 840mm deep \times 225mm high \rightarrow 0.173m². (36" wide \times 33" deep \times 8%" high \rightarrow 6.12ft²).

TOTAL CONNECTED LOAD DED OVER

LOTAL COMMECTED	ALME COMMECTED COND LEK CAEM:					
Supply	Nomin A3	al amps p A2:	or line A3	Total load kW		
240 voll. Two phase 240 voll. Three phase + N	20.83 12.00	20.88 21.00	12.00	10 10		

HEATING:

4 Tubular sheathed inner and outer elements at top and bottom of even each of 2.5kW giving a total of 10kW per oven.

SHIPPING DATA:

E700	m³ (packed) 1.05	ký (packéd 314
------	---------------------	-------------------

Our to commung predict improvement posts, the minuting our resolves the right to eller speed case is without prior notice.



Australia Moriet Pty Umead

Microsky/Trenspelle 149 Springlycle Road Malgrane, Victoria 1770 Theoretic 03-9518-3888 Teaching 03-9518-3883 Empl. Hoppstonumer and access modifictions as New South Water Telephore 02-8833-4111 Email remediac@modific comics

Source Australia Telephone 08-82/4 2115 Frod Ordinaguiettal.com so Conservational Newspapers 87-9630-8650 Email globales & modificación au

Western Australia Totaphone 03-9567 0369 Emer' perencimolity conven New Zeeland Wolful Limited

Chrisphore 03-388 1007 Errall sales@mo(fal.coms whose marting op or

Arckland Interhene 08 574 2150 Ernal -sales and fall color Mate, Weare 16 18 80



Property for the na

6 Соружура Маланала